

PRAMAC GSW 15

Item code: SC090SYA000



(purely indicative picture)



Main features

Standby power LTP : **10 kW**
Rated prime power (PRP) : **10 kW**
Rated continuous power (COP) : **kW**
Phases : **1**
Voltage : **230 V**
Frequency : **50 Hz**
Engine manufacturer : **Yanmar**
Fuel : **Diesel**
Speed governor : **Mechanical**

GSW 15-22 Series

This series provides the most professional way to fulfill small power requirements with highest reliability and excellent performance. Most popular range for residential areas and telecommunication sites.

Technical specifications

Main specifications

Type	Canopied
Standby power LTP	10 kVA
Standby power LTP	10 kW
Rated prime power (PRP)	10 kVA
Rated prime power (PRP)	10 kW
Rated continuous power (COP)	n.a.
Rated continuous power (COP)	n.a.

Phases	1
Voltage	230 V
Frequency	50 Hz
Battery charger current	40 A
Circuit breaker	50
Ratio	0,89

Engine specifications

Engine manufacturer	Yanmar
Model	3TNE88
Stroke	4, diesel
Fuel	Diesel
Number of cylinders and disposition	3, inline
Displacement	1642 cm ³
Air intake	Natural
Starting system	Electric
Nominal operating speed	1500 rpm
Speed governor	Mechanical
SAE	n.a.
Flywheel	n.a.
Continuous power COP	n.a.
Prime power PRP	12,3 kW
Standby power LTP	13,5 kW
Lube oil capacity	7,2 l
Coolant capacity	2 l
Fuel consumption at 100% PRP	3 l/h
Fuel consumption at 75% PRP	2 l/h
Maximum lube oil consumption at PRP	0,3 %
Electric circuit voltage	12 V
Engine derating	1,0
Cooling fan	Mechanical

Alternator specifications

Alternator manufacturer	MeccAlte
Model	ECO 28 S
Poles	4
Revolution speed	1500 rpm
Voltage	230 V
Frequency	50 Hz
Continuous nominal power at 40°C - COP	9,2 kVA

Continuous nominal power at 27°C - PRP	9,7 kVA
Standby power at 27 °C - LTP	10,3 kVA
Continuous active power at 27°C - PRP	10 kW
Efficiency at 75% load	81,5 %
Efficiency at 100% load	81,3 %
Maximum admitted overload	10% for 1 hour every 12 hours of running time S2
Voltage regulation system	Electronic
Alternator derating	1,0
Protection grade	IP 23

Additional information

Fuel tank location	Internal
Fuel tank capacity	55 l
Running time at 100% PRP	17,23 h
Running time at 75% PRP	23 h
Measured acoustic power (LWA) at 10 mt	n.a.
Noise level at 7 m	-25 dBA
Guaranteed noise level (LWA)	0 dBA

Dimensional data

Length	1800 mm
Width	830 mm
Height	1150 mm
Dry weight	660 kg