

PRAMAC GSW 65

Item code: SC400SDAW00



(purely indicative picture)



Main features

Standby power LTP : **44 kW**
Rated prime power (PRP) : **40 kW**
Rated continuous power (COP) : **40 kW**
Phases : **1**
Voltage : **230 V**
Frequency : **50 Hz**
Engine manufacturer : **Deutz**
Fuel : **Diesel**
Speed governor : **Mechanical**

GSW 65-170 Series

The GSW range is available with a range of accessories providing a versatile solution to a variety of applications e.g. to support Telecommunications sites.

Technical specifications

Main specifications

Type	Canopied
Standby power LTP	44 kVA
Standby power LTP	44 kW
Rated prime power (PRP)	40 kVA
Rated prime power (PRP)	40 kW
Rated continuous power (COP)	40 kVA
Rated continuous power (COP)	40 kW
Phases	1

Voltage	230 V
Frequency	50 Hz
Battery charger current	80 A
Circuit breaker	200
Ratio	0,95

Engine specifications

Engine manufacturer	Deutz
Model	BF4M2012 G2
Stroke	4, diesel
Fuel	Diesel
Number of cylinders and disposition	4, inline
Displacement	4040 cm ³
Air intake	Turbocharged
Starting system	Electric
Nominal operating speed	1500 rpm
Speed governor	Mechanical
SAE	n.a.
Flywheel	n.a.
Continuous power COP	49 kW
Prime power PRP	52 kW
Standby power LTP	58 kW
Lube oil capacity	8,5 l
Coolant capacity	15,9 l
Fuel consumption at 100% PRP	13 l/h
Fuel consumption at 75% PRP	9 l/h
Maximum lube oil consumption at PRP	0,15 %
Electric circuit voltage	12 V
Engine derating	1,0
Cooling fan	Mechanical

Alternator specifications

Alternator manufacturer	Stamford
Model	UCI 224E
Poles	4
Revolution speed	1500 rpm
Voltage	230 V
Frequency	50 Hz
Continuous nominal power at 40°C - COP	n.a.
Continuous nominal power at 27°C - PRP	40 kVA

Standby power at 27 °C - LTP	44 kVA
Continuous active power at 27°C - PRP	40 kW
Efficiency at 75% load	84,8 %
Efficiency at 100% load	83,2 %
Maximum admitted overload	10% for 1 hour every 12 hours of running time S2
Voltage regulation system	Electronic
Alternator derating	1,0
Protection grade	IP 23

Additional information

Fuel tank location	Internal
Fuel tank capacity	340 l
Running time at 100% PRP	26,88 h
Running time at 75% PRP	36 h
Measured acoustic power (LWA) at 10 mt	96 dBA
Noise level at 7 m	71 dBA
Guaranteed noise level (LWA)	97 dBA

Dimensional data

Length	2710 mm
Width	1180 mm
Height	1730 mm
Dry weight	1390 kg