



R16C

Engine MITSUBISHI , S4L2.SD
 Alternator LEROY SOMER , LSA422S4

STANDARD FEATURES

- Analog engine
- Simplified connection terminal block
- Four-pole breaker
- Central lifting ring

Voltage	Power ESP kWe/kVA	Power PRP kWe/kVA	Standby Amps
400/230	13 / 16	12 / 15	23



POWER DEFINITION

PRP : Prime Power is available for an unlimited number of annual operating hours in variable load applications, in accordance with ISO 8528-1. A 10% overload capability is available for a period of 1 hour within 12-hour period of operation, in accordance with ISO 3046-1 –

ESP : The standby power rating is applicable for supplying emergency power in variable load applications in accordance with ISO 8528-1. Overload is not allowed.

TERM OF USE

Standard reference conditions 25 °C Air Intlet Temp, 100 m A.S.L. 60 % relative humidity. All engine performance data based on the above mentioned maximum continuous ratings.

Type		dB(A)@1m	dB(A)@7m	Dimensions	Weight	Tank
	M126-DW	70.7	60.7	Long: 1797mm [71in] Wide: 775mm [31in] Height: 1391mm [55in]	672kg [1481lbs] Net 762kg [1679lbs] Gross	93 L
	M126	70.7	60.7	Long: 1750mm [69in] Wide: 715mm [28in] Height: 1230mm [48in]	610kg [1344lbs] Net 664kg [1463lbs] Gross	50 L

Base Rental Power + options suivantes = Full Rental Power

Double wall and great autonomy tank	Air inlet manifold preheating
Water separator pre-filter	Voltage trimmer
Fixed earth leakage protection with spike	Battery cut-out
Lub oil drain pump	



ENGINE SPECIFICATIONS

STANDARD FEATURES	Manufacturer / Model	MITSUBISHI S4L2.SD , 4-strokes, Athmo , N/A 4 X
	Cylinder Arrangement	L
	Displacement	1.75L [106.8C.I.]
	Bore and Stroke	92mm [3.6in.] X 78mm [3.1in.]
	Compression ratio	22 : 1
	Rated RPM	1500 Rpm
	Piston Speed	4.6m/s [15.1ft./s]
	Max. stand by Power at rated RPM	16.61kW [22BHP]
	Frequency regulation, steady state	+/-2. 5%
	BMEP	6.86bar [99psi]
Governor : type	Meca	
EXHAUST SYSTEM	Exhaust gas flow	410°C [770°F]
	Exhaust temperature	48.7L/s [103cfm]
	Max back pressure	700mm CE [28in. WG]
FUEL SYSTEM	110% (Stand By power)	N/A
	100% (of the Prime Power)	4.4L/h [1.2gal/hr]
	75% (of the Prime Power)	3.4L/h [0.9gal/hr]
	50% (of the Prime Power)	2.6L/h [0.7gal/hr]
	Max. fuel pump flow	18L/h [4.8gal/hr]
OIL SYSTEM	Total oil capacity w/filters	5.9L [1.6gal]
	Oil Pressure low idle	1bar [14.5psi]
	Oil Pressure rated RPM	4bar [58.0psi]
	Oil consumption 100% load	0.025L/h [0.0gal/hr]
	Oil capacity carter	5.4L [1.4gal]
THERMAL BALANCE	Heat rejection to exhaust	14kW [796Btu/mn]
	Radiated heat to ambient	2kW [114Btu/mn]
	Heat rejection to coolant	14kW [796Btu/mn]
AIR INTAKE	Max. intake restriction	200mm CE [8in. WG]
	Engine air flow	18.2L/s [39cfm]
COOLANT SYSTEM	Radiator & engine capacity	4.9L [1.3gal]
	Max water temperature	111°C [232°F]
	Outlet water temperature	93°C [199°F]
	Fan power	0.5 kW
	Fan air flow w/o restriction	0.8m ³ /s [1695cfm]
	Available restriction on air flow	10mm CE [0.4in. WG]
	Type of coolant	Gencool
Thermostat	82-95 °C	
GAS SYSTEM	HC	40 mg/Nm ³
	CO	120 mg/Nm ³
	Nox	1350 mg/Nm ³
	PM	100 mg/Nm ³



ALTERNATOR SPECIFICATIONS

GENERAL DATAS	Manufacturer / Type	LEROY SOMER LSA422S4
	Number of phase	3
	Power factor (Cos Phi)	0.8
	Altitude	< 1000 m
	Overspeed	2250 rpm
	Pole : number	4
	Exciter type	AREP
	Insulation : class, temperature rise	H / H
	Voltage regulator	R438
	Sustained short circuit current	1.4 AC
	Total harmonics (TGH/THC)	< 4%
	Wave form : NEMA = TIF – TGH/THC	< 50
	Wave form : CEI = FHT – TGH/THC	< 2%
	Bearing : number	1
	Coupling	Direct
	Voltage regulation 0 to 100% load	+/- 1%
	Recovery time (20% Volt dip) ms	500 ms
SkVA with 90% of nominal sustained voltage (at 0.4PF)	N/A	
OTHER DATAS	Continuous nominal rating @ 40°C	17.5 kVA
	Standby rating @ 27°C	21 kVA
	Efficiencies @ 4/4 load	87.6 %
	Air flow	0.15m ³ /s [317.83cfm]
	Short circuit ratio;50 (Kcc)	0.76
	Direct axis synchro reactance unsaturated (Xd)	160 %
	Quadra axis synchro reactance unsaturated (Xq)	80 %
	Open circuit time constant;50 (T'do)	410 ms
	Direct axis transient reactance saturated (X'd)	10.1 %
	Short circuit transient time constant (T'd)	30 ms
	Direct axis subtransient reactance saturated (X''d)	5 %
	Subtransient time constant (T''d)	3 ms
	Quadra axis subtransient reactance saturated (X''q)	7.1 %
	Zero sequence reactance unsaturated (Xo)	0.8 %
	Negative sequence reactance saturated (X2)	6 %
	Armature time constant (Ta)	4 ms
	No load excitation current (io)	0.6 A
	Full load excitation current (ic)	N/A
	Full load excitation voltage (uc)	36 V
	Recovery time (Delta U = 20% transitoire)	500 ms
	Motor start (Delta = 20% perm. Or 50% trans.)	51 kVA
	Transient dip (4/4 charge) – PF : 1.8 AR	13.6 %
No load losses	0.59kW [0.59Kw]	
Heat rejection	2 kW	

CONTROL PANEL

Standard



NEXYS

Specifications :
Frequency meter, Ammeter, Voltmeter
Alarms and faults Oil pressure, water temperature,
Overcrank, Overspeed (>60 kVA), Min/max alternator,
Low fuel level, Emergency stop
Engine parameters Hours counter, Engine speed,
Battery voltage, Fuel level, Air preheating

Option



TELYS

Specifications :
Frequency meter, Ammeter, Voltmeter
Alarms and faults Oil pressure, water temperature, No
start-up, Overspeed, Min/max alternator, Min/max
battery voltage, Low fuel level, Emergency stop
Engine parameters Hours counter, Oil pressure, Water
temperature, Engine speed, Battery voltage, Fuel level