

T25C2M

Stage 2
 Engine MITSUBISHI , S4S-Z263SD
 Alternator MECC ALTE , ECO 32-3S

STANDARD FEATURES

- Compliant with stage 2 of the european pollutant emissions directive
- Mechanical governor
- Mechanically welded chassis with antivibration suspension
- Power circuit breaker
- Radiator for wiring T° of 50°C [122°F] max with mechanical fan
- Protective grille for fan and rotating parts
- 9dB(A) silencer supplied separately
- Charged DC starting battery with electrolyte
- 12 V charging alternator and starter
- Supplied with oil and coolant -30°C
- User manual and commissioning guide



Voltage	Power ESP kWe/kVA	Power PRP kWe/kVA	Standby Amps	Dimensions	Weight
240MONO	25.0 / 25.0	22.7 / 22.7	104.2	Length: 1700mm [67in]	710kg [1565 lbs] Net
230MONO	25.0 / 25.0	22.7 / 22.7	108.7	Width: 896mm [35in]	820kg [1808 lbs] Gross
220MONO	25.0 / 25.0	22.7 / 22.7	113.6	Height: 1144mm [45in]	



POWER DEFINITION

PRP : Prime Power is available for an unlimited number of annual operating hours in variable load applications, in accordance with ISO 8528-1. A 10% overload capability is available for a period of 1 hour within 12-hour period of operation, in accordance with ISO 3046-1 –

ESP : The standby power rating is applicable for supplying emergency power in variable load applications in accordance with ISO 8528-1. Overload is not allowed.

TERM OF USE

Standard reference conditions 25 °C Air Intlet Temp, 100 m A.S.L. 60 % relative humidity. All engine performance data based on the above mentioned maximum continuous ratings.

Type	dB(A)@1m	dB(A)@7m	Dimensions	Weight	Tank
 M127	68.6	58.6	Length: 2080mm [82in] Width: 960mm [38in] Height: 1415mm [56in]	940kg [2072lbs] Net 1050kg [2315lbs] Gross	100 L
 M127-DW	68.6	58.6	Length: 2160mm [85in] Width: 966mm [38in] Height: 1582mm [62in]	1132kg [2496lbs] Net 1362kg [3003lbs] Gross	230 L





ENGINE SPECIFICATIONS

STANDARD FEATURES	Manufacturer / Model	MITSUBISHI S4S-Z263SD , 4-strokes, Athmo , [N/A] 4 X
	Cylinder Arrangement	L
	Displacement	3.33L [203.2C.I.]
	Bore and Stroke	94mm [3.7in.] X 120mm [4.7in.]
	Compression ratio	22 : 1
	Rated RPM	1500 Rpm
	Piston Speed	6m/s [19.7ft./s]
	Max. stand by Power at rated RPM	30.36kW [41BHP]
	Frequency regulation, steady state	< 5.5%
	BMEP	6.62bar [96psi]
Governor : type	MECA	
EXHAUST SYSTEM	Exhaust temperature	600°C [1112°F]
	Exhaust gas flow	103L/s [218cfm]
	Max back pressure	680mm CE [27in. WG]
FUEL SYSTEM	110% (Stand By power)	9.9L/h [2.6gal/hr]
	100% (of the Prime Power)	8.8L/h [2.3gal/hr]
	75% (of the Prime Power)	6.6L/h [1.7gal/hr]
	50% (of the Prime Power)	4.8L/h [1.3gal/hr]
	Max. fuel pump flow	36L/h [9.5gal/hr]
OIL SYSTEM	Total oil capacity w/filters	10L [2.6gal]
	Oil Pressure low idle	1bar [14.5psi]
	Oil Pressure rated RPM	5bar [72.5psi]
	Oil consumption 100% load	0.09L/h [0.024gal/hr]
	Oil capacity carter	9L [2.4gal]
THERMAL BALANCE	Heat rejection to exhaust	29kW [1649Btu/mn]
	Radiated heat to ambient	5kW [284Btu/mn]
	Heat rejection to coolant	29kW [1649Btu/mn]
AIR INTAKE	Max. intake restriction	250mm CE [10in. WG]
	Engine air flow	38L/s [81 cfm]
COOLANT SYSTEM	Radiator & engine capacity	8.9L [2.4gal]
	Max water temperature	100°C [212°F]
	Outlet water temperature	93°C [199°F]
	Fan power	0.7 kW
	Fan air flow w/o restriction	1m3/s [2119cfm]
	Available restriction on air flow	10mm CE [0.4in. WG]
	Type of coolant	Gencool
	Thermostat	76.5-90 °C
EMISSIONS LEVEL	PM	0.14 g/m3
	CO	0.19 g/m3
	Nox	0.77 g/m3
	HC	0.01 g/m3





ALTERNATOR SPECIFICATIONS

GENERAL DATAS	Manufacturer	MECC ALTE
	Type	ECO 32-3S
	Number of phase	1
	Power factor (Cos Phi)	1
	Altitude	1000
	Overspeed	[N/A]
	Pole : number	4
	Exciter type	NO
	Insulation : class, temperature rise	H / H
	Voltage regulator	AVR
	Total harmonics (TGH/THC)	[N/A]
	Wave form : NEMA = TIF – TGH/THC	[N/A]
	Wave form : CEI = FHT – TGH/THC	2
	Bearing : number	1
	Coupling	Direct
	Voltage regulation 0 to 100% load	[N/A]
	Recovery time (20% Volt dip) ms	[N/A]
	SkVA with 90% of nominal sustained voltage (at 0.4PF)	N/A
	OTHER DATAS	Continuous nominal rating @ 40°C
Standby rating @ 27°C		29 kVA
Efficiencies @ 4/4 load		87.4 %
Air flow		0.196m ³ /s [415.30cfm]
Short circuit ratio;50 (Kcc)		0.8
Direct axis synchro reactance unsaturated (Xd)		190 %
Quadra axis synchro reactance unsaturated (Xq)		98 %
Open circuit time constant;50 (T'do)		1.4 ms
Direct axis transient reactance saturated (X'd)		14.3 %
Short circuit transient time constant (T'd)		61 ms
Direct axis subtransient reactance saturated (X''d)		10 %
Subtransient time constant (T''d)		15 ms
Quadra axis subtransient reactance saturated (X''q)		30.6 %
Zero sequence reactance unsaturated (Xo)		2.7 %
Negative sequence reactance saturated (X2)		21.5 %
Armature time constant (Ta)		31 ms
No load excitation current (io)		[N/A]
Full load excitation current (ic)		[N/A]
Full load excitation voltage (uc)		[N/A]
Recovery time (Delta U = 20% transitoire)		[N/A]
Motor start (Delta = 20% perm. Or 50% trans.)		[N/A]
Transient dip (4/4 charge) – PF : 1.8 AR		[N/A]
No load losses		[N/A]
Heat rejection	[N/A]	



CONTROL PANEL

Standard



NEXYS

Specifications :

Frequency meter, Ammeter, Voltmeter
Alarms and faults Oil pressure, water temperature,
Overcrank, Overspeed (>60 kVA), Min/max alternator,
Low fuel level, Emergency stop
Engine parameters Hours counter, Engine speed,
Battery voltage, Fuel level, Air preheating

Option



TELYS

Specifications :

Frequency meter, Ammeter, Voltmeter
Alarms and faults Oil pressure, water temperature, No
start-up, Overspeed, Min/max alternator, Min/max
battery voltage, Low fuel level, Emergency stop
Engine parameters Hours counter, Oil pressure, Water
temperature, Engine speed, Battery voltage, Fuel level

